

CORSO LED N SE

Stropní LED svítidlo



[V] 220-240 AC	[Hz] 50	[°] 120	[m] ≥10000	[h] 20000	ellipse ≤ for Macadam	Ra 80
SMD			IP 44		[°C] -20+35	
	[mm²] 0,75-2,5	[m] max 10	[°] H360	[s] - [min] 5-10	micro wave	[lx] 25-2000
0,5m						



	[W]	[lm]	Tc [K]	
CORSO LED N 12-NW-SE 31099	12	800	4000	bílá
CORSO LED N 18-NW-SE 31100	18	1200	4000	bílá
CORSO LED N 24-NW-SE 31101	24	1600	4000	bílá

CORSO N LED jsou plafony vybavené integrovaným světelným zdrojem LED SMD. Plafony s označením SE jsou navíc vybaveny mikrovlnným senzorem pohybu. Tato svítidla mají stupeň krytí IP 44, což umožňuje montáž uvnitř i zvenku budovy.

- Materiál korpusu: plast
- Materiál difuzoru: PMMA



CORSO LED N 12-NW-SE




CORSO LED N 18-NW-SE




CORSO LED N 24-NW-SE

CORSO LED N SE


Stropní LED svítidlo



CORSO LED N 12-NW-SE



CORSO LED N 18-NW-SE



CORSO LED N 24-NW-SE